



Product Data Sheet

EP FAST 4T 20W 50

Performance: API SN || JASO MA2 Performance

Description: EP FAST 4T is designed specifically for high-temperature, high RPM, 4-stroke engines used in on and off-road motorcycles, ATVs and similar vehicles. It is a premium quality multi-grade engine oil designed with high-tech, low friction performance additives that deliver advanced low temperature fluidity to ensure easy cranking and start-up protection. It provides outstanding anti-wear protection, exceptional control and resistance of performance robbing sludge and varnish deposits and provides superior frictional characteristics for maximum power transfer, smooth shifting and superb wet clutch protection even under the most severe riding conditions.

Application: EP FAST 4T meets or exceeds API SN service classification and is compatible with all prior API classifications. EP FAST 4T 20W-50 Motorcycle Engine Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including JASO MA/MA2 many other OEM's specifications where a synthetic blend API SN motorcycle engine oil is recommended.

Benefits:

- For use in on / off-road 4-stroke motorcycles and ATVs
- Meets or exceeds API SN and JASO MA/MA2 service
- Resists breakdown in the most severe engine environments
- Fights formation of sludge and varnish deposits that reduce engine life
- Optimum protection over a wide operating temperature
- Excellent wear, corrosion, and rust protection
- Superior wet clutch protection

Characteristics:

Test Parameter	Test Method	Typical Value
API Gravity	ASTM D 287	29.7
Flash Point, COC °C/°F	ASTM D 92	206 / 402.8
Pour Point, °C/°F	ASTM D 97	-30 / -22
Viscosity @ 40°C, cSt	ASTM D 445	156.9
Viscosity @ 100°C, cSt	ASTM D 445	18.6
Viscosity Index	ASTM D 2270	133
CCS, mPa-sec °C max	ASTM D 5293	9500 @ -15
Total Base No. TBN	ASTM D 2896	7.9